# BID SPECIFICATIONS FOR NEW OR USED TRACK-MOUNTED COMPACT ZERO TURN HYDRAULIC EXCAVATOR FOR THE FLATHEAD COUNTY ROAD DEPARTMENT

#### UNIT MUST MEET OR EXCEED THE FOLLOWING SPECIFICATIONS:

### **GENERAL**

These specifications shall be construed as the minimum acceptable standards for a track-mounted hydraulic excavator. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment.

The use of specific names and numbers in specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of the County.

#### **BID PRICE**

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

## **MANUALS**

Each unit shall be provided with one (1) copy of the service manual, one (1) copy of the operator's manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

#### **ADDITONAL REQUIREMENTS**

All hydraulic and engine oil filters to be vertically mounted.

Extended life coolant shall be provided.

S.O.S. sampling ports (engine, hydraulics, transmission, coolant, and fuel).

Toolbox – 12" x 16" minimum.

Each bid shall include a recommended service interval schedule and an estimated fuel usage in gallons per hour.

Used machine must be newer than 2018 and have less than 1,500 hours.

Must have a dealership with parts and service department within 15 miles of Kalispell, Montana. All bids will be considered. Flathead County reserves the right to waive this requirement in the best interests of the County.

#### **WARRANTY**

Bidders shall submit a copy of the manufacturer's standard warranty, along with a complete explanation of what the warranty covers with their bid.

<u>WEIGHT</u> Minimum 32,000 lbs. Equipped with 28-inch wide shoes, bucket and thumb.	Yes No Page #
ENGINE Four (4) cylinder, tier 4, turbocharged minimum 180 cubic inch diesel engine v 90 net flywheel horsepower. Engine must be designed and built by or for the	e manufacturer.
	Yes No Page #
Shall be equipped with engine coolant heater – 110 Volt.	Yes No Page #
Engine air cleaner shall be dual element dry-type.	Yes No Page #
Shall be equipped with water separator.	Yes No Page #
Have ether starting aid.	Yes No Page #
STARTING SYSTEM Shall be equipped with a 24-volt electrical system with 45-amp alternator, heavy-duty starting motor.	Yes No Page #
Shall be equipped with a 12-volt converter cable capable of powering a 50 Watt two-way radio and CB.	Yes No Page #
<u>UNDERCARRIAGE</u> Track length shall be a minimum 11' feet.	Yes No Page #
Track shoe width shall be minimum 28".	Yes No Page #
Minimum seven (7) track rollers per side.	Yes No Page #
Minimum one (1) carrier roller per side.  CAPACITIES	Yes No Page #
Fuel Tank Capacity – 47 gallon minimum.	Yes No Page #
Hydraulic Tank Capacity – 15.9 gallon minimum.	Yes No Page #

Engine Coolant – 4 gallon minimum.	No
BOOM AND STICK One-piece boom with minimum 15' 1" length.	_No
Stick shall be a minimum of 8' 2" long.	No
<u>DIMENSIONS</u> Reach at ground level – 26 feet minimum.	No
Lifting capacity at ground level (15' over front) with bucket – min. 6,200 lbs.	_No
Lifting capacity at ground level (15' over side) with bucket – min. 6,200 lbs.	_ No
Bucket breakout force (SAE) – minimum 18,500 lbs.	No
Stick digging force (SAE) – minimum 13,000 lbs.	 No
BUCKET Bucket width – 30".	No
Bucket shall be general duty with minimum five (5) teeth and side cutters.	No
Bucket capacity – minimum 0.67 cubic yard capacity.	No
Bucket weight with teeth – minimum 800 lbs.	No
HYDRAULICS Hydraulic pump output shall be a minimum of 56 GPM.	No
<u>CAB</u> Enclosed ROPS cab: pressurized cab, rear-view camera.	_ No
Cab heater to provide outside filtered air circulation, multiple ducting to all windows.	No
Cab windows shall open for ventilation. Front and rear window wipers.	_No

Cab fresh air filters.	Yes	No
	Page #_	
Factory installed air conditioning.	Yes	No
	Page #_	
AM/FM Radio, Bluetooth capable.	Yes	No
	Page #_	
uspension Seat, with seat cover, and heated seat.	Yes	No
	Page #_	
BLADE		
Blade width – 8' 2" minimum.		_No
	Page #_	
	Yes	No
	Page #_	
Hydraulic up and down.	Yes	No
	Page #_	
With replaceable cutting edge.	Yes	No
	Page #_	
AUXILIARY HYDRAULICS  Machine shall include all valves bases and centrals to connect to budgaulic suite	adar ta r	in any type of
Machine shall include all valves, hoses, and controls to connect to hydraulic cylir hydraulic powered implements. Needs to have enough valves to run thumb and		
	Yes	No
Hydraulic full rotation thumb installed and connected to the optional hydraulics		
as described above.		No
OPTION 4	Page #_	
<b>OPTION 1</b> An extended powertrain warranty that covers an additional two to three years of	r	
an additional 2400 to 3600 hours, whichever occurs first. Include price for each.		No
	Page #_	
	Yes	No

**NOTE:** Award will be made on the basis of the total cost of the machine with all options included. However, Flathead County may, at its discretion, deduct one or more of the above-referenced options from the machine, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the machine.